



Headway Kreations Pvt. Ltd.

Product Type - 10W RGB Laser Light



Animation laser,DMX512, AUTO, Sound, ILDA,SD control,128 patterns ,ANG modulation ,with 40K scanner.

Technical specifications:			
Output red	3000mw/638nm		
Output green	3000mw/520nm		
Output blue	4000mw/445nm		
Scanner	with 40K		
laser class:	4		
operation modes:	animation laser, ILDA in/out ,X/Y axis ,power knobs,40K scanner		
basic patterns:	128		
beam specifications:	Color	Divergence	size at apertures
	Red:638nm	<1.2mrad	4*2mm
	Green:520nm	<1.2mrad	4*2mm
	Blue:445nm	<1.2mrad	4*4mm
Laser safety:	Laser safety according to EN 60825: Key switch, Interlock interface .Overload protection on X and Y Galva for best safeguarding against failure .Mechanical shutter optionally available.		
accessories:	power cable, manual, interlock adapter, key switch;		
power supply:	110-120V/220-240V switchable AC 50/60Hz		
power consumption:	120W		
Net weight	15KG with carton package,22KG with flight case		
Case Size(cm)	30.8cm*16.8cm*29.0cm		

Product Type - 12W RGB Laser Light



Animation laser,DMX512, AUTO ,Sound ,ILDA,SD control,128 patterns ,ANG modulation, with 40K scanner.

Technical specifications:			
Output red	4000mw/638nm		
Output green	4000mw/520nm		
Output blue	4000mw/445nm		
Scanner	with 40K		
laser class:	4		
operation modes:	animation laser ,ILDA in/out ,X/Y axis ,power knobs,40K scanner		
basic patterns:	128		
beam specifications:	Color	Divergence	size at apertures
	Red:638nm	<1.2mrad	4*2mm
	Green:520nm	<1.2mrad	4*2mm
	Blue:445nm	<1.2mrad	4*4mm
Laser safety:	Laser safety according to EN 60825: Key switch, Interlock interface .Overload protection on X and Y Galva for best safeguarding against failure .Mechanical shutter optionally available.		
accessories:	power cable, manual, interlock adapter, key switch;		
power supply:	110-120V/220-240V switchable AC 50/60Hz		
power consumption:	120W		
Net weight	17.3KG & 30KG with case		
Case Size(cm)	37*33.6*18.5cm		

Product Type - 15W RGB Laser Light



Animation ,DMX512, AUTO ,Sound, ILDA,SD control,128 patterns ,ANG modulation ,with 40K scanner

Technical specifications:			
Output red	4000mw/638nm		
Output green	5000mw/520nm		
Output blue	6000mw/445nm		
Scanner	with 40K		
class:	4		
operation modes:	ILDA in/out ,X/Y axis ,power knobs,40K scanner		
basic patterns:	128		
beam specifications:	Color	Divergence	size at apertures
	Red:638nm	<1.2mrad	4*2mm
	Green:520nm	<1.2mrad	4*2mm
	Blue:445nm	<1.2mrad	4*4mm
accessories:	power cable, manual, interlock adapter, key switch;		
power supply:	110-120V/220-240V switchable AC 50/60Hz		
power consumption:	120W		
Net weight	31KG & ,52KG with case		
Case Size(cm)	40x41x26cm		

Product Type - 20W RGB Laser Light



Specifications -

Lighting Type	LED
Usage/Application	Decoration
Wattage	20
Type Of Light	LED
Lighting Color	RGB
Material	metal
Body Material	Aluminum
Weight	10.820 kg
Weight With box	18.080 kg
Laser Color	RGB Multi -Colors+ single colors
Style	DMX Stage Light
Power	350W
Play mode	Auto, Sound active, DMX ,ELDA ,SD card
Power button	power and brightness adjustment
Accessories	power con cable, 4G SD card,manual,key,DB25 and RJ45 converter

Product Type - Pro RGB 24W



Animation laser ,ILDA control, ANG , IP52 protection rate ;Best quality adjustable holders and dichroic mirrors.

Technical specifications			
Output red	>6Wmw/638nm		
Output green	>8Wmw/520nm		
Output blue	>10W/445nm		
laser source:	ANG/TTL, DT50BB scanner		
operation modes:	Animation laser ,ILDA in/out, X/Y axis, power knobs		
basic patterns:	128		
beam specifications:	Color	Divergence	size at apertures
	Red	<1.3mrad	6*6mm
	Green	<1.3mrad	<5*5mm
	Blue	<1.3mrad	<4*4mm
Laser safety:	Laser safety according to EN 60825: Key switch, Interlock interface .Overload protection on X and Y Galva for best safeguarding against failure .Mechanical shutter optionally available.		
accessories:	power cable, manual, interlock adapter, key switch;		
power supply:	110-120V/220-240V switchable AC 50/60Hz		
power consumption:	120W		
weight	29KG net weight,46KG with case		
Case Size(cm)	37.6*33.2*26.7		

Product Type - 30W RGB Laser Light



Animation laser,ILDA control,ANG , IP52 protection rate;Best quality adjustable holders and dichro mirrors.

Technical specifications:			
Output red	>8Wmw/638nm		
Output green	>10Wmw/520nm		
Output blue	>12W/445nm		
laser source:	ANG/TTL, 50K scanner		
laser class:	4		
operation modes:	Animation laser,ILDA in/out, X/Y axis, power knobs		
basic patterns:	128		
beam specifications:	Color	Disvergence	size at aperature
	Red	<1.3mrad	4*2mm
	Green	<1.3mrad	<4*4mm
	Blue	<1.3mrad	<4*4mm
Laser safety:	Laser safety according to EN 60825: Key switch, Interlock interface.Overload protection on X and Y Galvo for best safeguarding against failure.Mechanical shutter optionally available.		
accessories:	power cable, manual, interlock adapter, key switch;		
power supply:	110-120V/220-240V switchable AC 50/60Hz		
power consumption:	120W		
weight	37KG net weight, 58KG with case		
Case Size(cm)	48cm*48cm*21.9cm		

Product Type - 40W RGB Laser Light



Specifications -

Lamp Efficiency(lm/w)	Luminous	155
Color Rendering Index(Ra)		90
Support Dimmer		Yes
Lifespan (hours)		10000
Working Time (hours)		10000
Input Voltage(V)		100~240V
Lamp Luminous Flux(lm)		10000
CRI (Ra>)		85
Working Temperature(°C)		-20 - 40
Working Lifetime(Hour)		10000
IP Rating		Ip44
Light Source		LED
Type		laser light
Power		40W
Color		RGB
Operation mode		Auto,Sound,ILDA,FB4,DMX512,Master/Slave
light sources		pure diode laser
IP rate		IP44

Product Type - 60W RGB Laser Light



Specifications -

Model NO	D1-RGB60W
Size	71 x 51 x 44 cm
Color	MULTICOLORED
Weight	36.444 kg
Weigh with Box	59.860 kg
Light Source	60W RGB Laser Diode
Emitting Color	RGB
Lamp Power	3000W
Laser Head Numbers	Single-head
Demonstration Effect	Animation
Control Mode	DMX512, Master/Slave, Sound Active, Auto, ELDA, Cat 5
Base	E27
Usage	Stage, Laser, Laser Module, Laser Pointer
Application	Outdoor
Operating Voltage	100-240V
Size	71 x 51 x 44 cm